

PRODUCT DETAILS

Index Number	11615
Wood Species	Oak
Pattern	1 strip
Grading	Village
Surface Colour	Grey

SURFACE

Surface coating	Extra Matt Lacquered 5 %, 7x Layers, >105 g/m2, BONA
Surface	Brushed
Bevel	2 side bevels

INSTALLATION

Installation Method	Floating or Glue-down to subfloor or concrete
Profile type	Uniclick

PRODUCT DIMENSIONS

Top layer	3 mm Oak Hardwood (+/- 0.2mm)
Middle layer	9.5 mm spruce
Bottom layer	1.5 mm birch veneer
Dimensions	14 x 180 x 1800-2000 mm
One pack includes	6 boards
Weight per 1 m2	≈ 8 kg
Pack might include	One start and end board allowed

TEST AND MARKS

CE mark and test by	Eph Dresden
Mark and icons	CE, EN14342:2005
Formaldehyde test	E1, M1



OAK VILLAGE GREY #11615

PARAMETERS

Under floor Heating	Yes (18-27 °C)
Warranty	30 years
Moisture content	6,5 % (+/-1%)

COLOUR CHANGE

Wood is a natural product - noticeable color change over time may occur

DETAIL DESCRIPTION

Healthy knots 50 mm
(diam. Up to)

Repaired knots 30 mm
(diam. Up to)

Sapwood allowed 30 mm
(width up to)

Discoloration No  High