

PRODUCT DETAILS

Index Number	21078
Wood Species	Ash
Pattern	1 strip
Grading	Elegant
Surface Colour	Onyx

SURFACE

Surface coating	Matt Lacquered 15-20 %, 7x Layers, >105 g/m2, BONA
Surface	Brushed
Bevel	2 side bevels

INSTALLATION


Installation Method	Floating or Glue-down to subfloor or concrete
Profile type	Uniclick

PRODUCT DIMENSIONS

Top layer	3 mm Ash Hardwood (+/- 0.2mm)
Middle layer	9.5 mm spruce
Bottom layer	1.5 mm birch veneer
Dimensions	14 x 160 x 1800-2390 mm
One pack includes	6 boards
Weight per 1 m2	≈ 8 kg
Pack might include	One start and end board allowed

TEST AND MARKS

CE mark and test by	Eph Dresden
Mark and icons	CE, EN14342:2005
Formaldehyde test	E1, M1



ASH ONYX #21078

PARAMETERS

Under floor Heating	Yes (18-27 °C)
Warranty	30 years
Moisture content	6,5 % (+/-1%)


COLOUR CHANGE

Wood is a natural product - noticeable color change over time may occur

DETAIL DESCRIPTION

Healthy knots 25 mm
(diam. Up to)

Repaired knots 25 mm
(diam. Up to)

Discoloration No  High